

1/11

FIG. 1





FIG. 2



3/11

FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D





FIG. 3E



4/11

FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D





FIG. 4E



5/11

FIG. 5A




FIG. 5B




FIG. 5C





FIG. 5D



6/11

FIG. 6A




FIG. 6B




FIG. 6C





FIG. 6D



7/11

FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D





FIG. 7E



FIG. 8




9/11

FIG. 9A


setting data		up	down	setting	
aging time	T	⬆	⬇	8888	min
aging voltage	Vs	⬆	⬇	8888	Volt
pulse-repetition frequency	f	⬆	⬇	8888	kHz
voltage applied to the data electrode	Vd	⬆	⬇	8888	Volt
pulse width	tw	⬆	⬇	8888	μ s
time delay	tc	⬆	⬇	8888	ns

FIG. 9B



10/11

FIG. 10



Reference numerals in the drawings

1, 100:	plasma display panel (panel)
2:	front substrate
3:	back substrate
4:	front glass plate
5, 5 ₁ – 5 _n :	scan electrode
6, 6 ₁ – 6 _n :	sustain electrode
7:	dielectric layer
8:	protecting layer
9:	back glass plate
10, 10 ₁ – 10 _m :	data electrode
11:	dielectric layer
12:	barrier rib
13:	phosphor layer
15, 15 ₁ – 15 _n :	scan electrode terminal section
16, 16 ₁ – 16 _n :	sustain electrode terminal section
17, 17 ₁ – 17 _n :	data electrode terminal section
18:	discharge cell
20:	discharge gap
21:	adjacent gap
100:	plasma display panel
110:	aging device
115, 116, 117:	short-circuit bar
120:	power supply section
130:	voltage waveform generator
140:	voltage waveform setting unit